



DOLOMITIC LIMESTONE PRO-SELECT PRILL

- *Corrects Soil pH*
- *Improved Nutrient Availability*
- *Adds Essential Magnesium & Calcium*
- *Activates Microorganisms*
- *100% Natural*
- *Will Not Burn*

 SOUTHDOWN, INC.

FOR PROFESSIONAL USE ONLY
NET WT. 50 LBS. (22.7 Kg)

DOLOMITIC LIMESTONE

176

6/28/00



DOLOMITIC LIMESTONE PRO-SELECT PRILL

GUARANTEED MINIMUM CHEMICAL ANALYSIS

ELEMENTAL CALCIUM (Ca)	21%
CALCIUM OXIDE (CaO)	29%
CALCIUM CARBONATE (CaCO ₃)	52%
ELEMENTAL MAGNESIUM (Mg)	10%
MAGNESIUM OXIDE (MgO)	17%
MAGNESIUM CARBONATE (MgCO ₃)	35%
CALCIUM CARBONATE EQUIVALENT (CCE)	93%
TOTAL OXIDES	46%
TOTAL CARBONATES	87%
EFFECTIVE NEUTRALIZING VALUE (ENV)	84%

F-1359

GUARANTEED MINIMUM PHYSICAL ANALYSIS (Before Pelletizing)

SCREEN SIZE	% PASSING
8 MESH	100%
10 MESH	100%
20 MESH	100%
40 MESH	99%
60 MESH	99%
80 MESH	98%
100 MESH	97%
200 MESH	93%
MOISTURE MAXIMUM	1%

CAS NUMBER - 16300-00-1

FLORIDA

This product requires 1930 pounds to equal 1 ton of standard lining material using calculated CCE. The guaranteed analysis is a minimum amount. Calcium carbonate, magnesium and CCE percentages may exceed those amounts.

NORTH CAROLINA

1940 pounds of this material equals 1 ton of standard lining material.

OHIO

Total Neutralizing Power (TNP) = 93.7 ENP - 1775 lbs/ton

PENNSYLVANIA

Agricultural Lining Material Classification - Fine Sized

TENNESSEE

Relative Neutralizing Value (RNV) = 81.6%

SUGGESTED SPREADER SETTING (Pounds per 1000 Square Feet)

	10#	20#	40#
CENTRAL 50	0-1/2	0	10
CYCLONE	5	7	9
EV-N-SPREAD	14-1/2	20	34
FRANCS	3	7-1/2	16-1/2
LESKO	J	N	9
SCOTTS SG 1	0	8-1/2	10
SCOTTS PPE/PP4 (DROP)	0-1/2	9	10
BEARS	3-1/2	4-1/2	6-1/2
BEARS (DROP)	5-1/2	7	10
SPYKER	4-1/2	5-1/2	6-1/2

*Requires 2 passes for recommended coverage

These settings are estimated. Actual settings depend on type, model & condition of spreader.

FOR INCORPORATION - AFTER APPLICATION - WET THOROUGHLY 30 MINUTES BEFORE TILLING

PRODUCT SAFETY INFORMATION WARNING

This product may contain greater than 0.05% silica which has been linked to chronic respiratory diseases. Repeated inhalation of respirable crystalline silica may have carcinogenic effects.

USE APPROVED RESPIRATOR IN DUSTY AREAS.
AVOID BREATHING MISBANCE DUST; USE WITH ADEQUATE VENTILATION.
FIRST AID: EYES-FLUSH WITH WATER; INHALATION - MOVE TO FRESH AIR
SEE MATERIAL SAFETY DATA SHEET (MSDS) FOR ADDITIONAL INFORMATION

SOUTHDOWN, INC.

Product Guaranteed by:
Southdown, Inc.
2200 Sullivan Trail
Easton, Penna. 18040
1-800-628-1763

Plants Located in: Castletown, VA & Paradise, PA



PRO-SELECT PRILL

Product/Brand